




	RELEASE DATE 2023.03.20 - REF EÇR 492			3 4 2	1		
Г	PARTS LIST			REVISION HISTORY	1		\neg
	ITEM QTY PART NUMBER DESCRIPTION	DATE	REV	DESCRIPTION	AUTHOR CH	HECKED BY APPROVI	ED
	1 1 505AC-5430-3 TUBE	08/17/16	PR3	REMOVED -19 AND -20; UPDATED LENGTH OF -5, -8, -12, -13, -15 AND -16; ADDED -40 ASSY AND -39 TUBE; CHNAGED LAST TWO BEND OF	JT LS	TL 6	
⊢	2 1 505AC-5430-6 FIRESLEEVE	00/17/10		-25.	J1 L	, , , , ,	_
⊢	3 2 AN818-8D NUT			NCREASED LENGTH OF -37, -36 AND -38; DECREASED LENGTH OF -9, -5, AND -8; ADDED -41 AND -44 ASSY; CHANGED ALL FIRESLEEVE TO			
⊢	4 2 AN819-8D SLEEVE 5 2 ES39502-2 FERRULE			BH-7; REMOVED -33 ASSY, -32 TUBE AND -34 FIRESLEEVE, -28 ASSY, -23 TUBE AND -31 FIRESLEEVE; ON THE -7, -9, -14, -17 AND -37 TUBE ASSY'S THE ES39500-1 FERRULE WAS CHANGED TO ES39502-2; ON -12 TUBE 6-3/8 IN TABLE CHANGED TO 5-7/16 AND TUBE LENGTH			
D	5 2 ES39502-2 FERRULE 6 2 PD80 CAPLUG - 1/2" X 3/4-16	04/06/17	A	HANGED FROM 10.20 TO 9.23; CHANGED TUBE DIMESIONS IN TABLE FROM INCHES TO FEET/INCHES; CHANGED LENGTH OF -06 WAS 64.07	JT LS	TU JT	D
⊢	0 2 FD00 CAFLOG - 1/2 X 3/4-10			-08 WAS 46.30 AND -16 WAS 39.48; ADDED MATERIAL INFO TO -6, -8, -13, -16, -38, -43; -39 TUBE FIRST STRAIGHT LENGTH WAS 1.07,			
				UPDATED TABLE AND OVERALL LENGTH WAS 21.85.			
		4/20/17	В	-24 FIRST TUBE SEGMENT LENGTH WAS 2.37.	EW LS	JT S	
		7/19/17	С	REV B AUTHOR WAS ETW, FILLED IN CHECKED BY AND APPROVED INITIALS REVS PR3 TO B.	EW LS	JT S	
		8/31/17	D	PD-80 CAPLUG ADDED TO -7,-9,-14,-17,-26,-37&-41. PD60 CAPLUG ADDED TO -27 & -30. PD40 CAPLUG ADDED TO -10,-11,-29,-40 & -44	PM LS	JT 3	
		3/29/18	E	IPDATED TUBE LENGTHS TO DECIMAL FORMAT; SHT. 10 -2 REVERSED ORDER OF BENDS; SHT 35-37 ADDED UPDATED ASSEMBLY TO AVOID	ZA LS	s мн	
	NOTE:			HARDPOINT			
	FLARE BOTH ENDS OF TUBE PER AS4330 AT ASSEMBLY.	6/20/18	F	SHT 36 UPDATED BEND 11 TANGENT ANGLE TO CUSTOMER PREFFERED, WAS 148.9 NOW 348.9	ZA LS	S MEH	_
٦		5/15/19	G	-21 TUBE: FIRST BEND LENGTH CHANGED TO 2.73" WAS 2.88"; -42 TUBE: CORRECTED FINAL DRAWING DIM FROM 1.53" TO 2.40" -43	ZA LS	S ZA	Г
		9/6/19		FIRESLEEVE: CHANGED CUT LENGTH WAS 14.80" NOW 14.37"; -44 ASSY: BOM WAS P/N 505AC-5430-45_A ,	70 10	. 74	_
	-	9/0/19	Н	-27 & -30 ASSY: ADDED ALTERNATE 086137 CAP PLUG -42 PART: CHANGED DRAWING VIEW AND FIXED LAST SEGMENT DIMENSION WAS 2.40" NOW 2.63", INCORRECT DIM DUE TO PREVIOUS	ZA LS	S ZA	_
		1/7/21	J	-42 PART: CHANGED DRAWING VIEW AND FIXED LAST SEGMENT DIMENSION WAS 2.40" NOW 2.63", INCORRECT DIM DUE TO PREVIOUS DRAWING VIEW ORIENTATION	ZA D	т МН	
	<u> </u>			ADDED YBC VALUES TO EVERY REFERENCE MANUFACTURING BEND TABLE AND ENSURED BEND ANGLE MATCHED MODEL DIMENSION; -42:	+ +		\dashv
		1/4/22	K	REVERTED ALL MODEL DIMENSIONS TO ORIGINAL TUBE MANUFACTURING DIMENSIONS	ZA D	T ZA	
	·			12 12 12 12 12 12 12 12 12 12 12 12 12 1			
cl							lc
							1
	6						
	$\sqrt{3}$						
+							₩
				-7 TUBE ASSEMBLY			
	(5)			7 TOBE AGGETIBET			
	\\						
	\\						
		(1					
В	\\	>	./				В
		(2	2)	(5)	6		
	\\	T					
		/					
		/					
		_ /					
			_				
		_	$\overline{}$				
╛				$\overline{\mathfrak{g}}$			\vdash
- 1				(4)			
				(4)			
				4)			
				(4)			
				(4)			
				(4)			
				Paravior® - Ti	rle .	DRAWING NUMBER	
Δ				<u>Falaviolis</u> Inc. PLUMBI	NG TUBE	drawing number 505AC-5430	
A				✓ Technology DIMENSIONS IN INCHES ASSE	NG TUBE MBLIES		
A				✓ Technology DIMENSIONS IN INCHES ASSE	NG TUBE MBLIES		A
A				DIRENTIOLOGY	NG TUBE IBLIES D APRVD. 1	505AC-5430 DATE REV ECC	A
A				DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED: .X = ±.1 .XX = ±.05 .XX = ±.05 .XX = ±.01 .XX = ±.01	NG TUBE MBLIES D APRVD. BY JT 6/1	505AC-5430 DATE REV ECC 7/16 K	A
A				DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED: .X = ±.1 .XX = ±.05 .XX = ±.05 .XX = ±.01 .XX = ±.01	NG TUBE MBLIES D APRVD. 1 DT 6/1 NOT SCALE DI	505AC-5430 DATE REV ECC 7/16 K RAWING SHEET	A 0
A				ASSE DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTES TOLERANCE TOL	NG TUBE ABLIES D APRVD. 1 BY 6/1 NOT SCALE DI 22 PARAVION TEX UTON IS A TRADE	505AC-5430 DATE REV ECT 7/16 K RAWING SHEET H. INC. 1 OF 37	A 0
Α	4			DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED: .X = ±.1 .XX = ±.05 .XX = ±.05 .XX = ±.01 .XX = ±.01	NG TUBE ABLIES D APRVD. 1 BY 6/1 NOT SCALE DI 22 PARAVION TEX UTON IS A TRADE	505AC-5430 DATE REV ECT 7/16 K RAWING SHEET H. INC. 1 OF 37	A 0






































RELEASE DATE 2023.03.20 - REF ECR 492 -16 FIRESLEEVE BH7 OR EQUIV. PER AS1072 AND UL94 V1 BURN TEST. A FIBERGLASS/SILICONE RUBBER MATERIAL. CUT LENGTH: 40.48" NOTES:
1. APPLY END DIP TO FIRESLEEVE ENDS, PARKER P/N 5027 (OR EQUIV.). 2. FIRESLEEVE: BENTLY HARRIS 241 SELSH POOL RD LOINVILLE, PA. 19353 (610)363-2600 DRAWING NUMBER $\frac{\text{Paravion}^{\$}}{\sqrt{\text{Technology}}}\text{Inc.}$ TITLE PLUMBING TUBE 505AC-5430 ASSEMBLIES REV ECO Κ SHEET PROTO 16 OF 37

